











RÄNDELSPEZIFIKATION/KNURLING SPECIFICATION

Ansicht View	Kennbuchstaben Distinguishing Letters	Rändelform Knurl shape
	RAA 0°	Rändel mit achsparellen Rillen knurl with grooves parallel to the axis
	RBL 30°	Linksrandel, Spiralwinkel 30° left-hand knurl, spiral angle 30°
	RBL 45°	Linksrandel, Spiralwinkel 45°, nicht in DIN 82 enthalten left-hand knurl, spiral angle 45°, not included in DIN 82
	RBR 30°	Rechtsrandel, Spiralwinkel 30° right-hand knurl, spiral angle 30°
	RBR 45°	Rechtsrandel, Spiralwinkel 45°, nicht in DIN 82 enthalten right-hand knurl, spiral angle 45°, not included in DIN 82
	RGE 30°	Links-rechts-Rändel, Spiralwinkel 30°, Spitzen erhöht left-hand right-hand knurl, spiral angle 30°, raised tips



RÄNDELSPEZIFIKATION/KNURLING SPECIFICATION

Ansicht View	Kennbuchstaben Distinguishing Letters	Rändelform Knurl shape
	RAA 0°	Rändel mit achsparellen Rillen knurl with grooves parallel to the axis
	RBL 30°	Linksrandel, Spiralwinkel 30° left-hand knurl, spiral angle 30°
	RBL 45°	Linksrandel, Spiralwinkel 45°, nicht in DIN 82 enthalten left-hand knurl, spiral angle 45°, not included in DIN 82
	RBR 30°	Rechtsrandel, Spiralwinkel 30° right-hand knurl, spiral angle 30°
	RBR 45°	Rechtsrandel, Spiralwinkel 45°, nicht in DIN 82 enthalten right-hand knurl, spiral angle 45°, not included in DIN 82
	RGE 30°	Links-rechts-Rändel, Spiralwinkel 30°, Spitzen erhöht left-hand right-hand knurl, spiral angle 30°, raised tips